

Modelo	CF25YR04	CF35MR04	CF50XS04	CF70BT04
Unidad interior	CF25YR04G	CF35MR04G	CF50XS04G	CF70BT04G
Unidad exterior	CF25YR04W	CF35MR04W	CF50XS04W	CF70BT04W

Refrigeración

Capacidad nominal (mín.-máx.)	kW	2,6 (1,0-3,0)	3,2 (1,0-4,0)	5,0 (1,0-6,0)	6,0 (1,6-7,2)
Consumo nominal	kW	0,75 (0,19-1,5)	0,94 (0,19-1,6)	1,54 (0,26-2,3)	2,06 (0,42-2,8)
EER		3,49	3,4	3,25	3,15
SEER		6,3	6,8	6,1	6,2
Clase energética		A++	A++	A++	A++

Calefacción

Capacidad nominal (mín.-máx.)	kW	2,7 (1,0-3,0)	3,3 (1,0-4,2)	5,6 (1,6-6,25)	7,1 (1,8-7,3)
Consumo nominal	kW	0,68 (0,19-1,5)	0,85(0,19-1,6)	1,55 (0,35-2,3)	2,15 (0,4-2,7)
COP		4,0	3,9	3,61	3,3
SCOP		4,0	4,0	4,0	4,0
Clase energética		A+	A+	A+	A+

Unidades interiores

Presión sonora (Alta/M.Alta/Media/M.Baja/Baja/Silencio)	dB (A)	39/37/34/32/29/24	39/37/34/32/30/24	44/42/40/37/36/31	45/42/40/38/35/32
Potencia sonora	dB (A)	57	57	59	64
Caudal de aire (Alta/M.Alta/Media/M.Baja/Baja)	m3/h	550/500/450/410/370	550/500/450/410/370	880/820/750/700/600	1100/950/880/800/700
Deshumidificación	l/h	0,9	1,2	2	2,2
Dimensiones (An x Al x Pr)	mm	795×256×197	795×256×197	890×300×223	998×325×225
Peso	kg	7,1	7,1	10	11

Unidades exteriores

Caudal de aire	m3/h	1500	2000	2200	2800
Presión sonora	dB (A)	51	52	55	56
Potencia sonora	dB (A)	62	62	63	65
Dimensiones (An x Al x Pr)	mm	660×483×240	780×540×260	810×585×280	860×667×310
Peso	Kg	21,5	25	34	41

Datos frigoríficos

Diámetro de tubería (Líq./gas)	Pulgadas/mm	1/4"/3/8" (6,35/9,52)	1/4"/3/8" (6,35/9,52)	1/4"/1/2" (6,35/12,7)	3/8"/5/8" (9,52/15,88)
Refrigerant		R32	R32	R32	R32
Precarga / Distancia	kg / m	0,48 / 5	0,66 / 5	1,15 / 5	1,32 / 5
Carga adicional	g/m	20	20	20	30
Longitud máxima	m	20	20	20	20
Desnivel	m	10	10	15	15
TCO2 eq		0,324	0,446	0,776	0,891

Datos eléctricos

Fuente de alimentación	V	220-240V~,50Hz,1P	220-240V~,50Hz,1P	220-240V~,50Hz,1P	220-240V~,50Hz,1P
Corriente nominal (refrigeración)	A	3,4	4,2	6,9	9,2
Corriente nominal (calefacción)	A	3	3,8	7	9,6

Rango de funcionamiento

Rango de funcionamiento (refrigeración)	°C	-15 ~ 43	-15 ~ 43	-15 ~ 43	-15 ~ 43
Rango de funcionamiento (calefacción)	°C	-20 ~ 24	-20 ~ 24	-20 ~ 24	-20 ~ 24